

PERFORMANCE BULLETIN



WORLD CAT 260CC-X

Length	25' 6"
Beam	9' 0"
Dry Weight (Boat Mfr. Pub)	5,600 lbs
Maximum HP	400 hp
Fuel Capacity	180 gal
Weight as Tested	7,708 lbs

F150XB / LF150XB

Horsepower	150 hp
Induction	EFI/DOHC
Displacement	2.8L
Weight (Estimated)	489 lbs
Gear Ratio	2.00:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position #3

PROPELLER(S)

Series	Reliance® Series
Diameter x Pitch	14-1/4 x 17
Yamaha Part #	68F-45972-20-00 / 68G-45972-20-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature	85° F / 78° F
(Fahrenheit)	85 1776 1
Elevation (in feet above sea level)	0'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes 90 gallons of fuel, 3 batteries, safety and test equipment.

YPB#: PB_WCC_260CC-X_TW_F150XB_7-1-2022_CAT



Engine: Yamaha F150XB / LF150XB

Boat: World Cat 260CC-X Configuration: Twin

Test Date: 30-Jun-2022



PERFORMANCE DATA

4.7 6.7 7.5 8.4 15.7	1.6 2.7 3.8 6.1 8.2	2.93 2.49 1.97 1.37 1.91
7.5 8.4 15.7	3.8 6.1	1.97 1.37
8.4 15.7	6.1	1.37
15.7		
	8.2	1.01
		1.91
21.8	10.4	2.09
27.1	12.7	2.12
31.3	16.2	1.93
35.3	19.7	1.79
39.6	25.2	1.57
44.1	31.0	1.42
	31.3 35.3 39.6	31.3 16.2 35.3 19.7 39.6 25.2

NOTICE TO CONSUMER The information and data

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's advelopting weight, wind and water conditions, temperature, humility, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance data on your specifications and performance data of this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamahas valuable trademarks. It may also contain trademarks belonging to the companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.